

REMARKS

The above amendment is believed to place the claims in proper condition for examination.  
Early and favorable action is awaited.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "Version with markings to show changes made."

In the event there are any additional fees required, please charge our Deposit Account No. 01-2340.

Respectfully submitted,

ARMSTRONG, WESTERMAN & HATTORI, LLP



William L. Brooks  
Reg. No. 34,129

Atty. Docket No. 020005  
Suite 1000  
1725 K Street, N.W.  
Washington, D.C. 20006  
Tel: (202) 659-2930  
WLB/yap

VERSION WITH MARKINGS TO SHOW CHANGES MADE

17. (Amended) A platen for a planar linear motor as set forth in any one of claims 10 to ~~16~~  
15, characterized in that said fluid hardening material is a molten metal material.

20. (Amended) A platen for a planar linear motor as set forth in any one of claims 10 to ~~16~~  
15, characterized in that said fluid hardening material is a molten resin material.

21. (Amended) A platen for a planar linear motor as set forth in any one of claims 10 to ~~16~~  
15, characterized in that said fluid hardening material is an adhesive.

22. (Amended) A platen for a planar linear motor as set forth in any one of claims 1 to ~~21~~  
15, characterized in that said magnetic sheets are blankings provided with platen dot use projections  
at every predetermined spatial period along one side edge.

23. (Amended) A platen for a planar linear motor as set forth in any one of claims 1 to ~~21~~  
15, characterized in that said platen dots are formed by hape-cutting electrodischarge machining the  
other parallel sheet edge surface of the stacked member.

24. (Amended) A platen for a planar linear motor as set forth in any one of claims 1 to ~~21~~  
15, characterized in that said platen dots are formed by etching one parallel sheet edge surface of the  
stacked member.

25. (Amended) A platen for a planar linear motor as set forth in any one of claims 1 to ~~24~~ 15, further provided with an outside frame abutting against at least the two side surfaces of the stacked member in the stacking direction and clamping the stacked member.

2005-07-08 14:00:00